

RCCN 日成SR型尼龙铆钉 SR Nylon Snap Rivet



材质：进口UL合格之NYLON66(黑色),防火等级94V-2,不易老化
 用法：先将机板及被固定板钻孔,再将本产品塞入压紧,即可使两板相结合。
 用途：PC板及机板之固定,取代螺丝,不需工具即可完成装配
 品质优良,做工精细。
 Material: NYLON66 UL approved, fireproof 94V-2
 Good quality, easy to install




FIG. 1
一字头
Single slot





FIG. 2
十字头
Across slot



单位/Unit:mm

型号/Item No.		装配孔径 Fix hole dia.	适用板厚 Suitable board thickness	拉力 Pull KG	尺寸 Dimensions					FIG. NO.	包装 Packing pcs
黑色/Black	白色/White	G	F		A	B	C	D	E		
SR2-2.4B	SR2-2.4W	2.1-2.2	0.6-1.2	3	4.2	1.2	2.4	2.0	2.8	1	1000pcs
SR2-3.2B	SR2-3.2W		1.3-2.0		4.2	1.2	3.2	2.0	3.8		
SR2-4.0B	SR2-4.0W		2.1-2.8		4.2	1.2	4.0	2.0	5.5		
SR2-4.8B	SR2-4.8W		2.9-3.6		4.2	1.2	4.8	2.0	5.5		
SR2-5.6B	SR2-5.6W		3.7-4.4		4.2	1.2	5.6	2.0	7.2		
SR2-6.4B	SR2-6.4W		4.5-5.2		4.2	1.2	6.4	2.0	7.1		
SR2.6-3.2B	SR2.6-3.2W	2.6-2.7	1.0-2.0	5	5.0	1.4	3.2	2.6	4.6	1	1000pcs
SR2.6-4.2B	SR2.6-4.2W		2.1-3.0		5.0	1.4	4.2	2.6	4.6		
SR2.6-4.8B	SR2.6-4.8W		2.7-3.6		5.0	1.4	4.8	2.6	6.2		
SR2.6-5.5B	SR2.6-5.5W		3.4-4.3		5.0	1.4	5.5	2.6	6.2		
SR2.6-6.4B	SR2.6-6.4W		4.3-5.2		5.0	1.4	6.4	2.6	7.8		
SR2.6-7.2B	SR2.6-7.2W		5.1-6.0		5.0	1.4	7.2	2.6	7.8		
SR3-3.5B	SR3-3.5W	3.1-3.2	1.0-2.0	8	6.4	1.6	3.5	3.0	5.1	1	1000pcs
SR3-4.5B	SR3-4.5W		2.0-3.0		6.4	1.6	4.5	3.0	5.1		
SR3-5.5B	SR3-5.5W		3.0-4.0		6.4	1.6	5.5	3.0	6.1		
SR3-6.5B	SR3-6.5W		4.0-5.0		6.4	1.6	6.5	3.0	6.1		
SR3-7.5B	SR3-7.5W		5.0-6.0		6.4	1.6	7.5	3.0	7.1		
SR3-8B	SR3-8W		5.5-6.5		6.4	1.6	8.0	3.0	7.1		
SR3-9B	SR3-9W		6.5-7.5		6.4	1.6	9.0	3.0	9.0		
SR3-10B	SR3-10W		7.5-8.5		6.4	1.6	10.0	3.0	11.0		
SR3-14.5B	SR3-14.5W		11.5-13.0		6.4	1.6	14.5	3.0	15.5		
SR3-23B	SR3-23W		20.5-21.5		6.4	1.6	23.0	3.0	24.0		
SR3.5-3.5B	SR3.5-3.5W	3.6-3.7	1.2-2.1	12	6.4	1.6	3.5	3.5	5.1	2	1000pcs
SR3.5-4.5B	SR3.5-4.5W		2.2-3.1		6.4	1.6	4.5	3.5	6.1		
SR3.5-5B	SR3.5-5W		2.7-3.6		6.4	1.6	5.0	3.5	7.1		
SR3.5-5.5B	SR3.5-5.5W		3.2-4.1		6.4	1.6	5.5	3.5	7.1		
SR3.5-6B	SR3.5-6W		3.7-4.6		6.4	1.6	6.0	3.5	7.1		
SR3.5-7B	SR3.5-7W		4.7-5.6		6.4	1.6	7.0	3.5	9.0		
SR3.5-8B	SR3.5-8W	5.7-6.6	6.4	1.6	8.0	3.5	9.0				
SR4-5B	SR4-5W	4.1-4.2	2.5-3.5	20	8.0	1.8	5.0	4.0	7.1	2	1000pcs
SR4-6B	SR4-6W		3.5-4.5		8.0	1.8	6.0	4.0	7.1		
SR4-7B	SR4-7W		4.5-5.5		8.0	1.8	7.0	4.0	9.0		
SR4-8B	SR4-8W		5.5-6.5		8.0	1.8	8.0	4.0	9.0		
SR4-9B	SR4-9W		6.5-7.5		8.0	1.8	9.0	4.0	11.0		
SR4-10B	SR4-10W		7.5-8.5		8.0	1.8	10.0	4.0	11.0		
SR4-12B	SR4-12W		9.0-10.5		8.0	1.8	12.0	4.0	14.0		
SR4-15.5B	SR4-15.5W		12.5-14.0		8.0	1.8	15.0	4.0	16.6		
SR5-4.5B	SR5-4.5W	5.1-5.2	1.5-2.5	25	9.0	2.2	4.5	5.0	6.5	2	1000pcs
SR5-5.5B	SR5-5.5W		2.5-3.5		9.0	2.2	5.5	5.0	6.5		
SR5-6.5B	SR5-6.5W		3.5-4.5		9.0	2.2	6.5	5.0	8.5		
SR5-7.5B	SR5-7.5W		4.5-5.5		9.0	2.2	7.5	5.0	8.5		
SR5-8.5B	SR5-8.5W		5.5-6.5		9.0	2.2	8.5	5.0	10.5		
SR5-9.5B	SR5-9.5W		6.5-7.5		9.5	2.2	9.5	5.0	10.5		
SR5-10.5B	SR5-10.5W	7.5-8.5	9.0	2.2	10.5	5.0	12.0	2	1000pcs		
SR6-6B	SR6-6W	6.1-6.2	2.5-4.0	30	12.0	2.5	6.0			6.0	9.0
SR6-8B	SR6-8W		4.0-5.5		12.0	3.0	8.0	6.0	10.0		